




**Pompe carellate monogiranti**  
**Single stage pumps**  
**trailer-mounted**



Serie  
Series

**CA**

Tipo Pompa Type Pump	Girante Impeller		Bocche Pompa Ports Pump		Giri presa forza R.P.M. PTO	Rapporto Ratio	Giri Pompa /1' R.P.M. Pump	Prestazioni Performance			Potenza Trattore Power Tractor HP
	ø mm.	apertura opening mm.	DNa	DNm				Portata Delivery l/1'	Prevalenza High head H mt.	Cv ass.	
<b>CA50-627C2</b>	195	6	65 mm.	50 mm.	638	1 : 6,27	4000	500 600 700 800 900	79,3 77 74,5 71 66,7	19,9 21,2 22,5 23,5 24,7	30
<b>CA50-627D2</b>	190	6	65 mm.	50 mm.	638	1 : 6,27	4000	500 600 700 800 900	74,1 71,3 68,7 65 60,7	18 19,3 20,5 21,4 22,5	30
<b>CA55-741A</b>	260	6	65 mm.	55 mm.	459	1 : 7,41	3500	500 600 700 800 900 1000	131 130 128 125 122 118	37 39,3 41,5 44 46 48,5	60
<b>CA55-741B</b>	250	6	65 mm.	55 mm.	459	1 : 7,41	3500	500 600 700 800 900 1000	120,7 119 117 115 111 106	33,5 35,5 37,5 39,5 42 43,5	60
<b>CA55-741C</b>	240	6	65 mm.	55 mm.	459	1 : 7,41	3500	500 600 700 800 900 1000	104 102 100 97 93 89	27 29 31 33 34,5 36	45
<b>CA55-628A</b>	260	6	65 mm.	55 mm.	557	1 : 6,28	3500	500 600 700 800 900 1000	131 130 128 125 122 118	37 39,3 41,5 44 46 48,5	60
<b>CA55-628B</b>	250	6	65 mm.	55 mm.	557	1 : 6,28	3500	500 600 700 800 900 1000	121 119 117 115 111 106	33,3 35,5 37,5 39,5 42 43,5	60
<b>CA55-628C</b>	240	6	65 mm.	55 mm.	557	1 : 6,28	3500	500 600 700 800 900 1000	104,2 102 100 97 93 89	27 29 31 33 34,5 36	45
<b>CA55-537A</b>	260	6	65 mm.	55 mm.	652	1 : 5,37	3500	500 600 700 800 900 1000	131 130 128 125 122 118	37 39,3 41,5 44 46 48,5	60
<b>CA55-537B</b>	250	6	65 mm.	55 mm.	652	1 : 5,37	3500	500 600 700 800 900 1000	121 119 117 115 111 106	33,3 35,5 37,5 39,5 42 43,5	60
<b>CA55-537C</b>	240	6	65 mm.	55 mm.	652	1 : 5,37	3500	500 600 700 800 900 1000	104,2 102 100 97 93 89	27 29 31 33 34,5 36	45
<b>CA65-738A1</b>	178	16	80 mm.	65 mm.	542	1 : 7,38	4000	800 900 1000 1100 1200 1300 1500	79,1 78,5 77,7 76,5 75,2 73,7 70,3	25,1 26,6 28 29,3 30,7 32 34,4	45