




Pompe carellate monogiranti
Single stage pumps
trailer-mounted



Serie
Series

CA

Tipo Pompa Type Pump	Girante Impeller		Bocche Pompa Ports Pump		Giri presa forza R.P.M. PTO	Rapporto Ratio	Giri Pompa /1' R.P.M. Pump	Prestazioni Performance			Potenza Trattore Power Tractor HP
	ø mm.	apertura opening mm.	DNa	DNm				Portata Delivery l/1'	Prevalenza High head H mt.	Cv ass.	
CA65-738B1	170	16	80 mm.	65 mm.	542	1 : 7,38	4000	800	66,7	20,5	35
								900	66	21,7	
								1000	65	22,8	
								1100	63,8	23,9	
								1200	62,3	25	
								1300	60,5	26	
1500	56,7	27,8									
CA65-627A1	178	16	80 mm.	65 mm.	638	1 : 6,27	4000	800	79,1	25,1	45
								900	78,5	26,6	
								1000	77,7	28	
								1100	76,5	29,3	
								1200	75,2	30,7	
								1300	73,7	32	
1500	70,3	34,4									
CA65-627B1	170	16	80 mm.	65 mm.	638	1 : 6,27	4000	800	66,7	20,5	35
								900	66	21,7	
								1000	65	22,8	
								1100	63,8	23,9	
								1200	62,3	25	
								1300	60,5	26	
1500	56,7	27,8									
CA65-741A2	260	9	80 mm.	65 mm.	459	1 : 7,41	3400	900	115	48,1	70
								1000	112	50,4	
								1100	111	52,7	
								1200	108,6	54,9	
								1300	106	57,2	
								1400	106	56	
CA65-741B2	250	9	80 mm.	65 mm.	459	1 : 7,41	3400	900	95	38	60
								1000	93	39	
								1100	90	41	
								1200	88	43	
								1300	85	45	
								1400	82	47	
CA65-741C2	240	9	80 mm.	65 mm.	459	1 : 7,41	3400	900	80	32,3	50
								1000	77,9	33,5	
								1100	75,6	35,3	
								1200	73,3	36,5	
								1300	71	38	
								1400	67	39,5	
CA65-628A2	260	9	80 mm.	65 mm.	541	1 : 6,28	3400	900	115	48,1	70
								1000	112	50,4	
								1100	111	52,7	
								1200	108,6	54,9	
								1300	106	57,2	
								1400	106	56	
CA65-628B2	250	9	80 mm.	65 mm.	541	1 : 6,28	3400	900	95	38	60
								1000	93	39	
								1100	90	41	
								1200	88	43	
								1300	85	45	
								1400	82	47	
CA65-628C2	240	9	80 mm.	65 mm.	541	1 : 6,28	3400	900	80	32,3	50
								1000	77,9	33,5	
								1100	75,6	35,3	
								1200	73,3	36,5	
								1300	71	38	
								1400	67	39,5	
CA65-537A2	260	9	80 mm.	65 mm.	633	1 : 5,37	3400	900	115	48,1	70
								1000	112	50,4	
								1100	111	52,7	
								1200	108,6	54,9	
								1300	106	57,2	
								1400	106	56	
CA65-537B2	250	9	80 mm.	65 mm.	633	1 : 5,37	3400	900	95	38	60
								1000	93	39	
								1100	90	41	
								1200	88	43	
								1300	85	45	
								1400	82	47	
CA65-537C2	240	9	80 mm.	65 mm.	633	1 : 5,37	3400	900	80	32,3	45
								1000	77,9	33,5	
								1100	75,6	35,3	
								1200	73,3	36,5	
								1300	71	38	
								1400	67	39,5	